


### THE EFFECT OF LFG PLASMA SPUTTERING POWER ON HARDNESS OF CARBON THIN FILMS ON SKD11 STEEL USING TARGET MATERIAL FROM BATTERY CARBON RODS


- 1. Regitrasi (12 Maret 2020)
- 2. Journal submission "Eastern-European Journal of Enterprise Technologies" (13 Maret 2020)
- 3. First revison with major reviison (13 Maret 2020)
- 4. Pengiriman kembali jurnal dengan perbaikan revisi (03 April 2020)
- 5. Second revision (09 April 2020)
- 6. Third revision (14 April 2020)
- 7. Accepted (20 April 2020)
- 8. Payment (29 April 2020)
- 9. Published (30 April 2020)

### **REGISTRASI EEJET JOURNAL**














### SUBMISSION EEJET JOURNAL






















### KORESPONDEN EEJET JOURNAL – JEJAK EMAIL



































### LICENSE AGREEMENT № \_\_\_\_\_ to use the work

Kharkiv "Malang, Indonesia" April 29, 2020

Aladin Eko purkuncoro, Rudy Soenoko, Dionysius Joseph Djoko Herry Santjojo, Yudy Surya Irawan (name of the author, co-authors)

(hereinafter referred to as the "Licensor" (Licensors)), on the one hand and PC "Technology Center", represented by the Director D.A. Demin, acting on the basis of the Charter (hereinafter referred to as the "Licensee"), on the other hand, have concluded the present Agreement as follows:

### **Definitions**

The terms, used in the present Agreement, shall have the following meaning:

*Work* is the scientific paper, offered by the Licensor for publication in the "Eastern-European Journal of Enterprise Technologies" (ISSN 1729-3774);

*Licensor* is the author (s) who has (have) the exclusive copyright to the Work;

*Nonexclusive license* is a license that does not preclude the Licensor from using the Work and issuance of licenses to use the Work to other parties.

Parties are the Licensee and the Licensor.

Other terms, used in the Agreement shall be determined according to the current legislation of Ukraine.

### 1. Subject of the Agreement

1.1. The **Licensor** grants the **Licensee** free of charge a non-exclusive license to use the work (of scientific, technical, or any other content) (hereinafter referred to as the "Work"), written in English language, under the conditions and for the period, specified in the present Agreement.

Title of the Work: The Effect of LFG Sputtering Power on Hardening of Carbon Thin Film on SKD11 Using Target Material From Battery Carbon Rods.

1.2. The **Licensor** guarantees that he/she has the exclusive copyrights to the Work, granted to the **Licensee**.

### 2. Property rights, granted to the Licensee

- 2.1. The Licensor grants the following rights to the Licensee for the whole period of the exclusive copyrights to the Work:
- 2.1.1. the right to reproduce the Work: publish in the journal "Eastern-European Journal of Enterprise Technologies" (hereinafter the Journal) in English language, disclose, duplicate, replicate or otherwise copy the Work without limiting the circulation of copies. In addition, each copy of the Work must contain the name of the Licensor;
  - 2.1.2. the right to distribute the Work in any way;
  - 2.1.3. the right to include in compound Works;
- 2.1.4. the right to make available to the public, including to place the entire Work or its any part in the Internet on the journal page and other information resources;
  - 2.1.5. the right to edit, adapt, or otherwise correct the Work without violating the content;
- 2.1.6. the right to translate the Work in the case when the Work is written in the language, different from that adopted in the Journal.
- 2.1.7. the right to use metadata (title, author name (copyright holder), summary, bibliographic materials, e-mail, work address etc.) of the Work by distribution and making available to the public, processing and systematization, as well as inclusion in various databases and information systems;
- 2.1.8. The Licensor grants to the Licensee a consent to transfer, storage and processing of his/her personal data without time restriction for their inclusion in the database according to the Law of Ukraine "On Personal Data Protection" No. 2297-VI dated June 1, 2010:
  - surname, name, patronymic;
  - data on academic qualifications (degree, academic rank);
  - data on the place of employment and post;
  - contact data of authors;
- data on the published works in national and international databases of scientific literature for their subsequent processing to perform search operations in these databases.

The personal data and metadata of the Work are presented for their storage and processing in various databases and information systems, their inclusion in analytical and statistical reporting, creation of reasonable interrelations of the objects of science, literature, and art with personal data, etc. in the territory, which is not limited. The Licensee has the right to transfer the specified data for processing and storage to the third parties under the condition of notifying on such a fact with the provision of the data on the third party (name and address) to the Licensor. Withdrawal of consent to the storage and processing of the personal data is made by the Licensor by sending the written notice to the Licensee.

2.2. The Licensor transfers the rights to the Licensee under the present Agreement on the basis of the non-exclusive license. The date of signing of the Agreement shall be the date of transfer of the rights under the present Agreement to the Licensee.

### 3. Territory of use

3.1. The territory on which it is allowed to use rights to the Work is not restricted.

### 4. The period, for which the rights are granted

- 4.1. The Agreement shall enter into force from the moment of its signing and is concluded for the period of 10 years, but no longer than the validity period of the exclusive property rights to the Work.
- 4.2. The validity period of the Agreement may be extended according to the current legislation of Ukraine.
- 4.3. In the case when the Work has not been accepted for publication or the Licensor has withdrawn the manuscript, the present Agreement expires.

### **5** . Liability of the Parties

- 5.1. The Licensor declares that:
- he/she is the author (co-author) of the Work;
- the copyrights to the Work were not transferred earlier and will not be transferred to third parties in the future;
- the present Work has not been published before and will not be published in any other edition before it is published by the Licensee;
- he/she has not violated any intellectual property rights of other parties. If the Work contains some materials of other parties, except for citations in the extent, justified by the scientific, information, or critical nature of the Work, the use of such materials shall be carried out by the Licensor in compliance with the legislation norms;
- he/she has obtained all necessary permissions to use the results, facts and other accepted materials, which do not represent the property of the Licensor;
- the Work does not contain information, not permitted for open publication according to the current legislation of Ukraine and publication and/or distribution of the Work by the Licensee will not result in disclosure of secret (confidential) information (including the state, official secret).
- 5.2. The Licensee shall undertake to observe the copyrights of the Licensor, provided by the current legislation, as well as to conduct their protection and take all possible measures to prevent copyright infringement by third parties.
- 5.3 The Licensee has the right to establish conditions of admission and publication of the Work in the Journal. The Editorial board of the Journal has the exclusive right to select or reject materials. The material carrier of the manuscript is not subject to return. The Editorial Board does not enter into correspondence regarding rejection of the Work, does not send reviews.
- 54. In all cases, not provided for by the present Agreement, the Parties shall be governed by the norms of current legislation of Ukraine.
- 55. The Party, which has unduly fulfilled or has not fulfilled its obligations under the present Agreement is obliged to compensate for the damages caused to the other Party, including lost profits.
- 5.6. The present Agreement is drawn up in two copies of identical content and equal legal force, one copy for each of the Parties.

### **6.** Other conditions

6.1. To ensure timely interaction under the present Agreement, the Party "Licensors" shall appoint from among themselves a representative under the present Agreement.

Such person is\_Aladin Eko Purkuncoro (Department of Mechanical Engineering, Technology of Nasional Institute Malang, Indonesia) contact tel. +62 81333292828.

6.2. The postal address for sending the journal Department of Mechanical Engineering, Technology of Nasional Institute Malang, Jl. Bendungan Sigura-gura No. 2, Malang 65145, Indonesia and its recipient Aladin Eko Purkuncoro

### Licensor (Licensors) Aladin Eko Purkuncoro PC "Technology Center" Shatilova dacha str., 4, Kharkiv, Ukraine, 61145 IBAN UA903515330000026004052313180 in KhMRA «Privatbank», Kharkiv EDRPOU 31886700 Licensor (Licensors) Rudy Soenoko Dionysius Joseph Djoko Herry Santjojo Yudy Surya Irawan (Filled and signed by all co-authors of the Work)

Director Demin D.

(l.s.)\*

\*The stamp

\*The stamp of the Personnel department or faculty, certifying the signatures of the Licensor (Licensors)

### Іпуоісе/Інвойс № 600/88-102-2020

Invoice Date: 28.04.2020	Дата інвойсу:28.04.2020
Supplier: PC «TECHNOLOGY CENTER» Address: 4 Shatilova Dacha Street, Kharkov, Ukraine, 61145	Виконавець: ПП «Технологічний Центр», Адреса: вул. Шатилова Дача, буд.4, м. Харків, 61145
Customer: Aladin Eko Purkuncoro Departement of Mechanical Engineering Institute Technology of Nasional Malang Jl. Bendungan Sigura-gura No. 2 Malang, Indonesia E-mail: aladin.eko.nurkuncoro@lecturer.itn.ac.id Contact Tel.: +6281333292828	3amonner: Aladin Eko Purkuncoro Departement of Mechanical Engineering Institute Technology of Nasional Malang Jl. Bendangan Sigara-guru No. 2 Malang, Indonesia E-mail: aladin.eko.nurkuncororofecturer.im.ac.id Contact Tel.: +6281333292828
Description: Payment for Publication of an article	Опие: Плата за послуги публікації
Currency: EUR	Валюта: євро
Price of the goods/services: 340,00	Ціна товарів/послуг: 340,00

### Bank information:

Beneficiary: PRIVAT COMPANY «TECHNOLOGY CENTER»

Account #:

IBAN: UA67 351533 00000 26006052124667

Beneficiary's bank: JSC CB "PRIVATBANK",

Bank Adress: 1D HRUSHEVSKOHO STR., KYIV, 01001, UKRAINE

SWIFT code: PBANUA2X

Ne	Description/ Orac	Quantity/ Kinskiers	Price/ Llina	Amount / Cyma
1	Publication of an article in a scientific journal «Eastern-European Journal of Enterprise Technologies», (ISSN (print) 1729-3774, ISSN(son-line) 1729-4861) No 2_2020: The EFFECT OF LIFE PLASMA SPUTTERING POWER ON HARDNIESS OF CARBON THIN FILMS ON SKORI STEEL USING TARGET MATERIAL FROM BATTERY CARRON BODS (Abdin Etc Parkuncon, Rudy Soeneko, Diospsias Joseph Djoko Berry Sanjoja, Yudy Surya Inwasi)  Hydenkanin cratrit y syponan "Eastern-European Journal of Enterprise Technologiess, (ISSN)print) 1729-3774, ISSN(on-line) 1729-4961) No 2_2020: THE EFFECT OF LIFE PLASMA SPUTTERING POWER ON HARDNIESS OF CARBON THIN FILMS ON SKOIT STEEL USING TARGET MATERIAL FROM BATTERY CARBON BODS (Abdin Etc Perhancons, Rudy Soeneko, Diospsias Joseph Djoko Berry Sanjoja, Yudy Sarya Inwas)	1	340,00 EUR/Capo	340,00 EUR/Capo
Tot	аl/ Усього:			340,00
	al to pay! Three hundred forty EUR 00 EUR/100 000 до СПТАТИ: Трыста сорок свро 00 центів			340,00

### Due 30/04/2020/ Сплатити до 30/04/2020

All charges of correspondent banks are at the Customer's expenses /Vci комісії банків-кореспоздентів сплачує Замовинк. The Customer makes payment upon acceptance of articles for publication within 10 banking days, according to this invoice. Payment under this invoice at the same time is the final proof of the acceptance of the manuscript to the publication in the "Eastern-European Journal of Enterprise Technologies". The fact of the execution of works and the provision of services in full, their acceptance, as well as confirmation of final settlements between the Parties is published article on the journal's site http://journals.uran.ua/eejet/issue/archive. Payment under this invoice is a confirmation that the Parties do not have mutual claims and do not intend to lodge a complaint.

Замовник здійснює оплату по факту прийняття Статті до публікації протягом 10 банківських диїв, згідно цього інвойсу. Оплати згідно цього рахунка-фактури (інвойсом) одночаєно є остаточним свідченням прийняття рукопису до опублікування до «Східно-Європейського журнату передових техностій». Фактом виконання робіт та надавня послут в повному обезді, їх прийняття, а також підтвердженням кінценну розрахунків між Сторонами є опубліковани стаття на свіїті журналу <a href="https://icumals.urap.un/ceiet/issue/archive">http://icumals.urap.un/ceiet/issue/archive</a> Оплата згідно цього рахунка-фактури (інвойсом) є підтвердженням того, що Сторони не мають взаємних претензій та не мають наміру направляти рекламації.

Supplier/ Виконавець:



(Demin D./Дьомін Д.)



## Tanggal/ Date: 29 APCL COLO Formulir Kiriman Uang Remittance Application

	Swift   KBANUA2	53	□ usp		Kurs/Rate Nilai/Total Amount	and the state of t	Valas/Amount in Kurs/ Nilai/ Foreign Exchange Amount	16. COO (15. COO)	C 2007 (10)	Suta transfer	-van lave	, Major,	Saya menyetujui sepenuhnya syarat-syarat yang tercantum pada halaman belakang formulir ini / lunconditiongliy gicept all the terms and conditions on the reyerse form.	ADMIN END PURKUNCOF
engretten-greizenen og mande, en engretnisk mit filmer	Jenis Pengiriman/ $\square$ LLG/ <i>Clearing</i> $\square$ DI Type of Transfer $\square$ RTGS	Sumber Dana/ Source of fund Cek/BG No.  Tunai/Cash Debit Rek./Debit Acc. No.	Mata Uang/Currency:   IDR	Jumlah Dana yang dikirim/Amount Transfer:	Jumlah/Amount Kur	45 7×7	Biaya/Charge Yoriga	Komisi/Commision Pengiriman/Handling Bank Korespondent Bank	Jumlah Biaya/Amount Charge :	Tool	1 told Meling trans Prise	Sepanin Cu		Peiabat Bank/Bonk Office Teller
AREAS TRANSPORTED TO THE CHILD SECTION OF THE CONTRACT OF THE	Penduduk/ Bukan Penduduk/ Resident Non Resident	center)	Alamat/Address: 4SHATILOVA DACHA STIEGT Mata	AREON Negara/Country: UPA/INE	Ban	100	No. Rek./Acc. No.: U. A. 67 35 1575 00000 260005212413	sonal   Perusahaan/Company	IN EKO PUPKUNCORO	Nama Allas/Allos Name: ACAVIIIO No. 10: 357347 005 780011 Terb	mma putra godba 11 to 22, Sulm	Telepon/Phone: BIFFIN 1938 Negara/Country: IN povest4	Tujuan Transaksi (Transaction Purpose): Publication Of An article Orival (PETET) PANT (155N 1720-3774) PANT (155N 17	pebankan ke rekening/ : for account of :   Pengirim/Remitter   Sharing

Apin Eld MIKLINCORD Pemohon/Applicant olent value must fill in the PMN (KYC) Form.

Lembar 1: Bank Lembar 2: Lembar 3: Nasabah

Pejabat Bank/Bank Office

PT. BANK NECARA INDONESIA (Persero), Tbk CABANG : UNIBRAW MALANG

· IBOC - Maintenance (S10

: 02421 : 29/04/2020 : 13:03:42

\*Sender's Reference:

:32A:200429EUR340, Ordering Customer:

:50K:/0000000234052533 BPK ALADIN EKO PURKUNCORO

JL TANJUNG PUTRA YUDHA II NO 22B

4 SHATILOVA DACHA STREET

KHARKOV'UKRAINE

Sender to Receiver Information:

:72://ACC/AT/YR JSC CB PRIVATBANK



REFERENCE : S10UBM00022020 /

NO. TRX.: 82421 936310 96963 TRAN 29/04/2020 12:48:06

NO. REK.: 000000234052533 Bpk ALADIN EKO PURKUNC JUMLAH: 1DR 543,590-1568

253 - UNIBRAW MALANG

NO. TRX.: 82421 936310 96963 TRAN 29/04/2020 12:48:06
NO. REK.: 253360420801001 PENDAPATAN PROPISI KU
JUMLAH: IDR 35,000 1568
253 - UNIBRAW MALANG 82421 936310 96963 TRAN 29/04/2020 12:48:06

NO. TRX.: 82421 936310 96963 TRAN 29/04/2020 12:48:06
NO. REK.: 253360482010001 Pendapatan Restitusi B
JUMLAH: IDR 508,590 1568

NO. TRX.: 82421 936310 96963 TRAN 29/04/2020 12:48:06
NO. REK.: 0000000234052533 Bpk ALADIN EKO PURKUNC
JUMLAH: IDR 5,764,020- 1568
253 - UNIBRAW MALANG

NO. TRX.: 82421 936310 96963 TRAN 29/04/2020 12:48:06
NO. REK.: 253333200101001 KU YAKIR EUR
JUMLAH: EUR 340 1568
253 - UNIBRAW MALANG



Акумуляторні відходи – це відходи, які можуть завдати шкоди навколишньому середовищу, і в Індонезії досі не налагоджена їх якісна переробка. Хоча відходи батарей містять вуглець, який може бути використаний в якості цільового матеріалу для осадження вуглецевих плівок з використанням плазмового розпилення. Метою даного дослідження є визначення ефекту і оптимального значення потужності генерації плазмового аргону для отримання максимального значення твердості стали SKD11, що забезпечує вироблення потужності. В даному методі використовується плазма у вигляді аргону. Аргонова плазма генерується з використанням LGF 40 кГц. Тонка плівка вуглецю, що синтезується на сталі SKD11, була випробувана для визначення величини твердості з використанням мікротвердості по Віккерсу. Виходячи з результатів експерименту, оптимальна потужність, отримана при 340 Вт з найвищим середнім значенням твердості, становить 316,7 HV. Грунтуючись на спостереженні SEM-EDX, можна описати, що порівняння атомарного вуглецю з вуглецевих стрижнів без обробки (1,5 %) і вуглецевих тонких плівок на SKD11 з оптимальною енергетичної обробкою (13,36 %) показує різні значення. Кількість атомарного вуглецю тонких плівок на SKD11 з енергетичної обробкою вище, ніж у атомарного вуглецю вуглецевих стрижнів без обробки, обумовлює більш високе значення твердості тонких плівок на сталі SKD11 після обробки плазмовим напиленням за оптимальними енергетичними параметрами, ніж у сталі SKD11 без обробки. Сталь SKD11, що має високе значення твердості, що використовується в якості штампів і різання, вимагає високих показників твердості

Ключові слова: сталь SKD11, плазмове напилення, акумуляторні стрижні, потужність, LGF, твердість, аргон, осадження, тонкі плівки, вуглець **UDC 621** 

DOI: 10.15587/1729-4061.2020.198474

## THE EFFECT OF LFG PLASMA SPUTTERING POWER ON HARDNESS OF CARBON THIN FILMS ON SKD11 STEEL USING TARGET MATERIAL FROM BATTERY CARBON RODS

Aladin Eko Purkuncoro

Departement of Mechanical Engineering Institute Technology of Nasional Malang Jl. Bendungan Sigura-gura No. 2, Malang, Indonesia, 65145 E-mail: aladin.eko.purkuncoro@lecturer.itn.ac.id

Rudy Soenoko

Professor\*

E-mail: rudysoen@ub.ac.id

Dionysius Joseph Djoko Herry Santjojo

Associate Professor

Department of Physical\*\* E-mail: dsantjojo@ub.ac.id

Yudy Surya Irawan

Associate Professor\*

E-mail: yudysir@ub.ac.id

\*Department of Mechanical Engineering\*\*

\*\*Brawijaya University

Jl. Mayjend Haryono, 167, Malang, Indonesia, 65145

Received date 13.03.2020 Accepted date 20.04.2020 Published date 30.04.2020 Copyright © 2020, Aladin Eko Purkuncoro, Rudy Soenoko,
Dionysius Joseph Djoko Herry Santjojo, Yudy Surya Irawan
This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0)

### 1. Introduction

Zinc carbon battery rods have been widely used for several applications, such as toys, remote control, radio and cameras. Every year battery waste increases. But the increase in the amount of battery waste is not balance with recycle processing of battery waste. Even though, carbon rod from waste of Zinc-Carbon battery contains Aluminum (Al) and Iron (Fe) which are harmful to human health and the environment [1–3]. Actually in modern batteries don't use Pb and Hg already in water. This will certainly endanger to human health [4, 5]. Good recycling of carbon batteries will contribute to improving environmental quality. Previous studies used carbon rods for graphene oxide and biogas [3, 4]. Whereas carbon rods of batteries can be used for carbon layer deposition as a source of carbon.

Amorphous carbon layer has been widely used in industry and research. The amorphous carbon layer has a wide variety of properties of mechanical, physical, biomedical, and

tribological so that it can be utilized in broad applications as well [6–8]. Carbon atoms that have sp<sup>3</sup> hybridization have stronger bonds, so as to increase the hardness value of the thin layer of carbon material [7].

Previous research of carbon films were successfully synthesized using CVD plasma, hollow-cathode plasma and plasma sputtering [8]. Plasma sputtering has several advantages when compared to the other method, such as high deposition rate, low substrate temperature, and produce best quality thin film at lower substrate temperatures [10, 11]. Plasma sputtering bombards the target with energized particles, so that the ions from the carbon of the target material will come out and be deposited on the substrate. One of technique for carbon deposition in materials is low frequency 40 kHz plasma sputtering. The frequency is suitable for the plasma sputtering technique because the 40 kHz LFG generator has the highest ion density value of the two other plasma generator frequencies, 13.36 MHz and 2.45 GHz, so that more plasma particles are formed per square inch than

generators others [11]. Changes of ion density cause changes in ion bombardment of the target material for deposition of thin films [8, 10].

One of gas that is suitable for use in plasma sputtering is argon gas. Argon is an inert noble gas, which means it will form very little or no chemical compounds. In argon gas the dominant influence in plasma sputtering is a physical reaction. Argon atoms are heavy atoms with low reactive properties, so it would be more effective if used to target materials for deposition of thin films [8, 11].

Recently, the use of steel as a material in the industrial world and machinery has developed rapidly. Steel in the market generally has limited mechanical performance. One example is SKD11 steel which only has a hardness of 58–60 HV [13]. Though SKD11 steel is widely used as dies, forming, and cutting so it requires high hardness performance [13, 14].

The highest chemical content of SKD11 steel is carbon (C) [15]. The hardness of steel can also be increased by increasing the carbon content of the steel [16]. One of the ways to increase carbon content can be done by coating the steel with amorphous carbon [17]. The amorphous carbon layer is attractive to researchers because of its good mechanical properties such as low coefficient of friction, hardness and high durability [18]. The hardness performance of SKD11 steel can be improved by deposition of an amorphous carbon layer by plasma sputtering process [19].

Previous research on deposition of carbon thin film on glass substrate using material target from battery carbon rods with plasma sputtering show that the carbon was successfully deposited onto glass substrate. It was proved by FTIR results, C-C and C=C was formed [1]. In the view of all these, argon plasma sputtering to deposition carbon thin film using material target from battery carbon rods may provide a new efficient approach to improve the mechanical properties of films. There is great scope to work on this topic further.

In the other studies, microstructural changes and hardness variations in SKD11 steel have been investigated during the processes of carbide dispersion (CD). However, the process of carbide dispersion carburizing requires high temperatures at 980 °C and the process takes a long time for 120 min. The process certainly requires a greater cost that plasma sputtering. Even though, plasma sputtering is more simple and cheaper than carburizing method to improve hardness performance of SKD11 steel. However, the investigation plasma sputtering process for hardening SKD11 steel was limited. On the other sides, SKD11 steel has limited hardness performance of 58-60 HV. Even though, the steel is commonly used for industrial purposes which require a high hardness performance. Therefore, studies that are devoted to obtain the maximum average of hardness value of carbon thin films on SKD11 steel with optimization of argon gas power parameter on plasma sputtering.

### 2. Literature review and problem statement

Plasma is the fourth phase form of matter after solid, liquid, and gas [20]. Plasma is formed due to ionization. Plasma can be applied as a method for deposition of thin films [12]. One application of carbon deposition is carried out on steel. Synthesis of thin films has been carried out using plasma enhanced chemical vapor deposition, plate parallel hollow cathode plasma with radio frequency, and plasma sputtering.

Based on these 3 methods, plasma sputtering has several advantages compared to other methods such as high deposition rates, low substrate temperatures, and synthesis high quality of thin films [8, 11]. Plasma sputtering works by utilizing high energy of plasma species as bombers of target materials [21].

Steel that is often used for industry, generally has limited mechanical performance. Many of research are done to improve steel mechanical performance [19]. One of the examples is research of increasing the hardness value of AISI H13 steel. The results of research indicate that increasing the hardness value with the increasing carbon content of AISI H13 steel [22]. Besides AISI H13 steel, there is steel that often used in the industrial world, such as SKD11 steel [23]. SKD11 steel is often used for dies, forming, and cutting [15]. However, SKD11 steel still has weaknesses. SKD11 steel has low hardness, around 58–60 HV [13]. Based on these problems, research has to do to increase the value of steel hardness. One of the ways is deposition carbon thin films on SKD11 steel with plasma sputtering.

Power is an important role in the process of plasma sputtering [19, 23]. The higher the power, the stronger the electric field that is formed, and the greater ion energy. If the energy of ion is greater than the binding energy of the target material's atoms, the atoms of the target material will be detached from the bonds of the atoms and move in all directions. The atom of the target material that comes out is called a sputtered atom [10]. Sputtered atom will be deposited on surface substrate and thin films structure that is formed will affect to the hardness of substrate [1].

A similar study about the effect of plasma sputtering RF power on diamond-like carbon thin films was previously had been carried out by Jongwannasiri et al. Based on the results of the study showed plasma treatment on DLC films surface influenced to thickness change, but not affect to structure of the films with various RF powers [24]. However, the limitation of this result didn't discuss about the effect of various plasma power on hardness of DLC films and only discuss the thickness of DLC films. Even though, Björling et al, found that the thicker deposited carbon thin film on substrate will have a high probability of carbon content [25]. In addition, Concepción et al, also found that the greater value of carbon content in carbon thin films, the greater value of hardness [16]. Therefore in this study, deposition carbon thin films with plasma sputtering for hardening SKD11 is done by using material target from battery carbon rods and determine effect power of plasma connected with hardness of carbon thin films on SKD11.

### 3. The aim and objectives of research

The aim of research is to investigate plasma sputtering process to increasing hardness of carbon thin films on SKD11 steel.

To achieve this aim, the following objectives are accomplished:

 to observe plasma power affected on hardness of carbon thin films on SKD11 steel.

### 4. Experimental method

### 4. 1. Sample preparation

Material target that used in this research was prepared by carbon rod from zinc-carbon ABC battery waste (ABC Battery Industry, made in Indonesia). The carbon rod was cut into reach diameter 8 mm and length 55 mm. Then, the carbon rod was cleaned by ultrasonication with 40 kHz and 360 W in soap, solution for 1 minute. The cleaned carbon rod was dried in the oven at 300  $^{\circ}$ C for 2 hours. The substrate used is SKD11 steel. Before plasma sputtering process, the substrate was cleaned by technical alcohol.

### 4. 2. Deposition thin film

Carbon films were deposited using plasma sputtering. Plasma is generated by low frequency generator (LFG) 40 KHz. The plasma system has diameter chamber of 250 mm. The carbon rod as material target was placed at the electrode. Carbon rods as a target material are placed on the electrodes. The distance between the target material and SKD11 steel is kept at 1.7 cm. The argon gas was introduced with flow rate of 20 mL/min into the chamber after vacuum process of 1.5 hours. The power used for generation varies 300 W, 340 W, 380 W, 420 W and 460 W. The deposition is done for 2 hours, keeping the temperature at 300 °C. The illustration scheme of the plasma sputtering system used in this research is shown in Fig. 1 and plasma sputtering process on vacuum chamber shown in Fig. 2.




Fig. 1. Scheme of the plasma sputtering system




Fig. 2. Plasma sputtering process on vacuum chamber

### 4. 3. Characterization

The hardness value of SKD11 steel that has been deposited with carbon thin films on SKD11 with power treatment was tested using micro hardness Vickers at three different test points shown as Fig. 3. The hardness value of SKD11 steel is obtained by taking the average hardness value from measurements at three test points that have been done pre-

viously. The content and morphology of the carbon rod and thin films carbon on SKD11 steel with plasma sputtering treatment on optimum power parameters of 340 W was measured using scanning electron microscope/energy dispersive using X-ray (SEM-EDX).




Fig. 3. Micro hardness vickers at three different test points on carbon thin films on SKD11 steel


### 5. Research results of hardness value of carbon thin films on SKD11 steel and SEM EDX

The hardness value of SKD11 steel that has been deposited with carbon film with power variations was tested with micro hardness Vickers to determine the effect of power on the plasma sputtering process on the hardness of SKD11 steel. The results of the SKD11 steel hardness test using micro hardness Vickers are shown in Table 1, Fig. 4.

Table 1
The hardness value of carbon thin films on SKD 11 steel after power of plasma sputtering treatment based on the microhardness Vickers test

Test Point	Hardness Value (HV) Carbon thin films with Power				
	300 W	340 W	380 W	420 W	460 W
1	253.1	328.3	279.8	265.3	248.8
2	262.2	309.1	268.1	260.2	247.7
3	262.8	312.7	283.2	271.5	256.4
Average of hardness	259.3	316.7	277.0	265.7	251.0

Average of hardness value of SKD 11 steel after power of plasma sputtering treatment based on the microhardness vickers test



Average of hardness value

Linear (Average of hardness value)

Fig. 4. Graph of hardness value of SKD11 Steel with power treatment

SEM imaging of carbon rods and carbon thin film on SKD11 after plasma treatment with optimum power parameter of 340 W shown in Fig. 5, 6.

SEM observation was carried out on the outermost part of carbon rods from ABC battery waste shown as Fig. 5. The red line of Fig. 5 is an area that shows composition of battery carbon rods shown as Table 2. Based on SEM-EDX results shown as Table 2, atomic carbon level of carbon rods has 81.94 %.




Fig. 5. SEM imaging of carbon rods outer layer from ABC battery waste

Table 2
Compositions of battery carbon rods based on SEM-EDX results

Element	Atomic %
С	81.94
О	13.98
Al	0.98
Si	1.16
Cl	0.54
K	0.34
Ca	0.43
Fe	0.63




Fig. 6. SEM imaging of carbon thin film on SKD11 steel after plasma sputtering treatment with optimum power parameter of 340 W

Table 3 shown carbon purity level of thin film on SKD11 steel after plasma sputtering treatment with optimum parameter of  $340~\rm W.$ 

Table 3

Compositions of carbon thin film on SKD11 steel after plasma sputtering treatment with optimum power parameter of 340 W based on SEM-EDX results

Element	Atomic %
Cr	15,76
Mn	1,32
Fe	54.51
Ni	5.73
Si	0,90
O	8,32
С	13,36
V	0,11

### 6. Discussion of the research results of hardness value of carbon thin films on SKD11 steel and SEM EDX

It follows from Table 1 that the variation of power on plasma from 300 to 340 Watt increases the average of hardness value of carbon thin films on SKD11 steel, from 259.3 HV increased to 316.7 HV. However, power variations from 380 W, 420 W and 460 W have decreased hardness at  $380~\mathrm{W}$  to  $460~\mathrm{W},$  from  $277~\mathrm{HV}$  to  $251~\mathrm{HV}.$  The treatment of power on plasma sputtering with highest average hardness value is obtained at power of 340 W with 361.7 HV. Fig. 4 shows that downtrend on graph of relationship SKD11 steel with power treatment. Based on the graph shown as Fig. 4, the hardness value has a tendency to decrease when the power on plasma sputtering increases. This is because power is related to plasma energy. The greater the power causes the greater argon ion energy. It causes the transfer of energy from plasma to carbon atoms. As a consequence, carbon atoms have more energy when the power on plasma sputtering is greater. High-energy carbon atoms will tend to re-reflect or reflect rather than forming bonds or deposited on the surface. While at too low a power the carbon atom does not have enough energy to form carbon bonds on surface of SKD11 steel. At optimum power, the carbon atom is not too energetic but the energy it possesses is also not too small. As a result, the carbon bonds formed on the surface SKD11 steel are higher than the other power parameters. It can be seen in Fig. 7 which shows an illustration of the movement of carbon atoms from carbon rods on SKD11 steel substrates.

As follows from the Table 2 and Fig. 4, however, if this refers to previous research that solved the problem of successfully depositing carbon of carbon rod from waste of ABC battery which has 81.94 % of atomic carbon on a glass substrate using plasma sputtering [1]. Based, on these results, the carbon of carbon rods from ABC battery waste has potential to be used as a target material for deposition of carbon thin films on SKD11 steel substrate.

Based on surface morphology, the outer surface of the carbon rod has a rougher shape than the outer surface of carbon thin films on SKD11 (Fig. 5, 6.). Based on the previous reference, the atomic carbon of SKD11 steel without treatment is 1.5 %. Table 3 shows that if the atomic carbon of thin film on SKD11 after plasma treatment with optimum power parameter of 340 W compared with the carbon con-

tent of SKD11 steel without treatment based on reference. Atomic carbon content in thin films on SKD11 with power treatment (13.36%) is higher than atomic carbon content on SKD11 steels without treatment (1.5%). Carbon impurities in thin films affect the value of hardness. High carbon impurities indicate that concentrations of atoms that are not same type are high. The higher carbon impurities deposited on SKD11 steel, cause more smaller possibility bonding between carbon and carbon on SKD11 steel. This bond is covalent bonds which is a strong bond and requires high energy to break the bond. More covalent bonds cause increasing the hardness of carbon thin films on SKD11.




Fig. 7. Main signature: a — deposition of carbon atoms at low power; b — deposition of carbon atoms at optimum power; c — deposition of carbon atom at high power;  $\Phi$  — carbon atom;  $\Phi$  — direction of carbon atom;  $\Phi$  — atom of SKD11 steel

The advantages of this research compared to the other similar research, studies that are more discuss the effect of LFG plasma sputtering power with hardness value of SKD11 steel and obtain the maximum average of hardness value of carbon thin films on SKD11 steel with optimization of argon gas power parameter on plasma sputtering. Previous research, about the effect of plasma sputtering RF power on diamond-like carbon thin films had been carried out. However, the limitation of this result didn't discuss about the effect of various plasma power on hardness of DLC films and only discuss the thickness of DLC films [25]. The other

studies also have been carried out by deposition of carbon thin film with LFG plasma sputtering power treatment of 220 W, 260 W, 320 W, and 340 W on glass using battery carbon rods as target. But, the result only discuss about FTIR results of carbon sputtering with various power [1].

The shortcomings and restrictions of the research, SKD11 without treatment are not tested by micro hardness Vickers to determine the hardness value. So that comparison of the hardness value of SKD11 steel without treatment is based on previous research as references and SEM-EDX is only tested on the most optimum power parameters of 340 W. Plasma sputtering system in this study still uses manual systems and there are no pressure gauge sensors of plasma sputtering system.

There are several things that can be developed in this research. Increased range of power variations (100–500 W) and measure the hardness value for each power variations. Pressure gauge can be added to know the value of pressure in the chamber of plasma sputtering system.

### 7. Conclusion

Experiment study of deposition carbon thin film on SKD11 with power on plasma sputtering treatment had been investigated to determine hardness performance. Based on micro hardness test, the optimum power treatment obtained at 340 Watt with the highest average hardness value is 316.7 HV. At optimum power, the carbon atom is not too energetic but the energy it possesses is also not too small. Based on SEM-EDX observation, it can be described that comparison of atomic carbon from carbon rods without treatment (1.5 %) and carbon thin films on SKD11 with optimum power treatment (13.36 %) show different value. Number of atomic carbon of thin films on SKD11 with power treatment is higher than atomic carbon of carbon rods without treatment.

### References

- Purkuncoro, A. E., Santjojo, D. J. D. H., Irawan, Y. S., Soenoko, R. (2019). Deposition of Carbon Thin Film by Means of a Low-Frequency Plasma Sputtering Using Battery Carbon Rods as a Target. IOP Conference Series: Materials Science and Engineering, 515, 012041. doi: https://doi.org/10.1088/1757-899x/515/1/012041
- 2. Klotz, K., Weistenhöfer, W., Neff, F., Hartwig, A., van Thriel, C., Drexler, H. (2017). The Health Effects of Aluminum Exposure. Deutsches Aerzteblatt Online, 114 (39), 653–659. doi: https://doi.org/10.3238/arztebl.2017.0653
- 3. Tanong, K., Blais, J.-F., Mercier, G. (2014). Metal Recycling Technologies for Battery Waste. Recent Patents on Engineering, 8 (1), 13–23. doi: https://doi.org/10.2174/1872212108666140204004041
- Nindhia, T. G. T., Surata, I. W., Atmika, I. K. A., Negara, D. N. K. P., Artana, I. P. G. (2015). Processing Carbon Rod from Waste of Zing-Carbon Battery for Biogas Desulfurizer. Journal of Clean Energy Technologies, 3 (2), 119–122. doi: https://doi.org/10.7763/jocet.2015.v3.179
- Nindhia, T. G. T., Surata, I. W., Atmika, I. K. A., Negara, D. N. K. P., Artana, I. P. G. (2015). Processing Carbon Rod from Waste of Zing-Carbon Battery for Biogas Desulfurizer. Journal of Clean Energy Technologies, 3 (2), 119–122. doi: https://doi.org/10.7763/jocet.2015.v3.179
- 6. Erdemir, A., Donnet, C. (2006). Tribology of diamond-like carbon films: recent progress and future prospects. Journal of Physics D: Applied Physics, 39 (18), R311–R327. doi: https://doi.org/10.1088/0022-3727/39/18/r01
- 7. Chu, P. K., Li, L. (2006). Characterization of amorphous and nanocrystalline carbon films. Materials Chemistry and Physics, 96 (2-3), 253–277. doi: https://doi.org/10.1016/j.matchemphys.2005.07.048
- 8. Mori, T., Sakurai, T., Sato, T., Shirakura, A., Suzuki, T. (2016). Growth process of hydrogenated amorphous carbon films synthesized by atmospheric pressure plasma enhanced CVD using nitrogen and helium as a dilution gas. Japanese Journal of Applied Physics, 55 (4), 045503. doi: https://doi.org/10.7567/jjap.55.045503
- 9. Wen, F., Liu, J., Xue, J. (2017). The Studies of Diamond-Like Carbon Films as Biomaterials: Review. Colloid and Surface Science, 2 (3), 81–95.

- Abdelrahman, M. M. (2015). Study of Plasma and Ion Beam Sputtering Processes. Journal of Physical Science and Application, 5 (2). doi: https://doi.org/10.17265/2159-5348/2015.02.007
- Plasma Technology (2007). Available at: https://pdf.directindustry.com/pdf/diener-electronic/plasma-technology-diener-electronic/ 50802-410101.html
- Hammadi, O. (2015). Fundamentals of Plasma Sputtering. Nanophotonics and Nanodevices Fabricated by Magnetron Sputtering Technique. doi: http://doi.org/10.13140/RG.2.1.3855.5605
- 13. General Catalog of YSS Tool Steels (2015). Available at: https://www.hitachi-metals.co.jp/e/products/auto/ml/pdf/yss\_tool\_steels\_d.pdf
- 14. Yu, Z., Wang, Z. G., Yamazaki, K., Sano, S. (2006). Surface finishing of die and tool steels via plasma-based electron beam irradiation. Journal of Materials Processing Technology, 180 (1-3), 246–252. doi: https://doi.org/10.1016/j.jmatprotec.2006.06.014
- 15. Kong, J. H., Sung, J. H., Kim, S. G., Kim, S. W. (2006). Microstructural Changes of SKD11 Steel during Carbide Dispersion Carburizing and Subzero Treatment. Solid State Phenomena, 118, 115–120. doi: https://doi.org/10.4028/www.scientific.net/ssp.118.115
- 16. De la Concepción, V. L., Lorusso, H. N., Svoboda, H. G. (2015). Effect of Carbon Content on Microstructure and Mechanical Properties of Dual Phase Steels. Procedia Materials Science, 8, 1047–1056. doi: https://doi.org/10.1016/j.mspro.2015.04.167
- 17. Calik, A., Duzgun, A., Sahin, O., Ucar, N. (2010). Effect of Carbon Content on the Mechanical Properties of Medium Carbon Steels. Zeitschrift Für Naturforschung A, 65 (5), 468–472. doi: https://doi.org/10.1515/zna-2010-0512
- 18. Jones, B. J., Anguilano, L., Ojeda, J. J. (2011). Argon plasma treatment techniques on steel and effects on diamond-like carbon structure and delamination. Diamond and Related Materials, 20 (7), 1030–1035. doi: https://doi.org/10.1016/j.diamond.2011.06.004
- Mróz, W., Burdyńska, S., Prokopiuk, A., Jedyński, M., Budner, B., Korwin-Pawlowski, M. L. (2009). Characteristics of Carbon Films Deposited by Magnetron Sputtering. Acta Physica Polonica A, 116, S-120–S-122. doi: https://doi.org/10.12693/aphyspola.116.s-120
- 20. Miyamoto, K. (2000). Fundamentals of Plasma Physics and Controlled Fusion. Available at: http://people.physics.anu.edu.au/~jnh112/AIIM/c17/Miyamoto.pdf
- González, J. M., Bertran, E. (2015). Mechanical and Surface Characterization of Diamond-Like Carbon Coatings onto Polymeric Substrate. Available at: https://arxiv.org/ftp/arxiv/papers/1509/1509.08512.pdf
- 22. Telasang, G., Dutta Majumdar, J., Wasekar, N., Padmanabham, G., Manna, I. (2015). Microstructure and Mechanical Properties of Laser Clad and Post-cladding Tempered AISI H13 Tool Steel. Metallurgical and Materials Transactions A, 46 (5), 2309–2321. doi: https://doi.org/10.1007/s11661-015-2757-z
- 23. Aizawa, T., Fukuda, T. (2013). Oxygen plasma etching of diamond-like carbon coated mold-die for micro-texturing. Surface and Coatings Technology, 215, 364–368. doi: https://doi.org/10.1016/j.surfcoat.2012.07.095
- Jongwannasiri, C., Watanabe, S. (2014). Effects of RF Power and Treatment Time on Wettability of Oxygen Plasma-Treated Diamond-like Carbon Thin Films. International Journal of Chemical Engineering and Applications, 5 (1), 13–16. doi: https://doi.org/10.7763/ijcea.2014.v5.342
- Björling, M., Larsson, R., Marklund, P. (2014). The Effect of DLC Coating Thickness on Elstohydrodynamic Friction. Tribology Letters, 55 (2), 353–362. doi: https://doi.org/10.1007/s11249-014-0364-6

# THE EFFECT OF LFG PLASMA SPUTTERING POWER ON HARDNESS OF CARBON THIN FILMS ON SKD11 STEEL USING TARGET MATERIAL FROM BATTERY CARBON RODS

by Aladin Eko Purkuncoro

Submission date: 12-Nov-2020 06:17AM (UTC+0700)

**Submission ID: 1443332561** 

File name: 1. ARTIKEL EEJET SUDAH PUBLIS 2020.pdf (1.05M)

Word count: 4719

Character count: 23635

Акумуляторні відходи - це відходи, які можуть завдати шкоди навколишньому середовищу, і в Індонезії досі не налагоджена їх якісна переробка. Хоча відходи батарей містять вуглець, який може бити використаний в якості цільового матеріали для осадження вуглецевих плівок з використанням плазмового розпилення. Метою даного дослідження є визначення ефекту і оптимального значення потужності генерації плазмового аргону для отримання максимального значення твердості стали SKD11, що забезпечує вироблення потужності. В даному методі використовується плазма и вигляді аргони. Аргонова плазма генериється з використанням LGF 40 кГц. Тонка плівка вуглецю, що синтезується на сталі SKD11, була випробувана для визначення величини твердості з використанням мікротвердості по Віккерсу. Виходячи з результатів експерименту, оптимальна потужність, отримана при 340 Вт з найвищим середнім значенням твердості, становить 316,7 HV. Трунтуючись на спостереженні SEM-EDX, можна описати, що порівняння атомарного вуглецю з вуглецевих стрижнів без обробки (1,5 %) і вуглецевих тонких плівок на SKD11 з оптимальною енергетичної обробкою (13,36 %) показує різні значення. Кількість атомарного вуглецю тонких плівок на SKD11 з енергетичної обробкою више, ніж и атомарного вуглещо вуглецевих стрижнів без обробки, обумовлює більш високе значення твердості тонких плівок на сталі SKD11 після обробки плазмовим напиленням за оптимальними енергетичними параметрами, ніж у сталі SKD11 без обробки. Сталь SKD11, що має високе значення твердості, що вико-

Ключові слова: сталь SKD11, плазмове напилення, акумуляторні стрижні, потужність, LGF, твердість, аргон, осадження, тонкі плівки, вуглець

\_

ристовується в якості штампів і різання, вимагає

UDC 621

DOI: 10.15587/1729-4061.2020.198474

## THE EFFECT OF LFG PLASMA SPUTTERING POWER ON HARDNESS OF CARBON THIN FILMS ON SKD11 STEEL USING TARGET MATERIAL FROM BATTERY CARBON RODS

Aladin Eko Purkuncoro

Departement of Mechanical Engineering Institute Technology of Nasional Malang

Jl. Bendungan Sigura-gura No. 2, Malang, Indonesia, 65145 E-mail: aladin.eko.purkuncoro@lecturer.itn.ac.id

Rudy Soenoko

Professor\*

E-mail: rudysoen@ub.ac.id

Dionysius Joseph Djoko Herry Santjojo

Associate Professor

Department of Physical\*\* E-mail: dsantjojo@ub.ac.id

Yudy Surya Irawan

Associate Professor\*

E-mail: yudysir@ub.ac.id

\*Department of Mechanical Engineering\*\*

\*\*Brawijaya University

Jl. Mayjend Haryono, 167, Malang, Indonesia, 65145

Received date 13.03.2020 Accepted date 20.04.2020 Published date 30.04.2020

високих показників твердості

opyright © 2020, Aladin Eko Purkuncoro, Rudy Soenoko, 1 pnysius Joseph Djoko Herry Santjojo, Yudy Surya Irawan

 $This is an open access article \ under the \ CC\ BY\ license\ (http://creativecommons.org/licenses/by/4.0)$ 

### 1. Introduction

Zinc carbon battery rods have been widely used for several applications, such as toys, remote control, radio and cameras. Every year battery waste increases. But the increase in the amount of battery waste is not balance with recycle processing of battery waste. Even though, carbon rod from waste of Zinc-Carbon battery contains Aluminum (Al) and Iron (Fe) which are harmful to human health and the environment [1–3]. Actually in modern batteries don't use Pb and Hg already in water. This will certainly endanger to human health [4, 5]. Good recycling of carbon batteries will contribute to improving environmental quality. Previous studies used carbon rods for graphene oxide and biogas [3, 4]. Whereas carbon rods of batteries can be used for carbon layer deposition as a source of carbon.

Amorphous carbon layer has been widely used in industry and research. The amorphous carbon layer has a wide variety of properties of mechanical, physical, biomedical, and

tribological so that it can be utilized in broad applications as well [6–8]. Carbon atoms that have sp<sup>3</sup> hybridization have stronger bonds, so as to increase the hardness value of the thin layer of carbon material [7].

Previous research of carbon films were successfully synthesized using CVD plasma, hollow-cathode plasma and plasma sputtering [8]. Plasma sputtering has several advantages when compared to the other method, such as high deposition rate, low substrate temperature, and produce best quality thin film at lower substrate temperatures [10, 11]. Plasma sputtering bombards the target with energized particles, so that the ions from the carbon of the target material will come out and be deposited on the substrate. One of technique for carbon deposition in materials is low frequency 40 kHz plasma sputtering. The frequency is suitable for the plasma sputtering technique because the 40 kHz LFG generator has the highest ion density value of the two other plasma generator frequencies, 13.36 MHz and 2.45 GHz, so that more plasma particles are formed per square inch than

generators others [11]. Changes of ion density cause changes in ion bombardment of the target material for deposition of thin films [8, 10].

One of gas that is suitable for use in plasma sputtering is argon gas. Argon is an inert noble gas, which means it will form very little or no chemical compounds. In argon gas the dominant influence in plasma sputtering is a physical reaction. Argon atoms are heavy atoms with low reactive properties, so it would be more effective if used to target materials for deposition of thin films [8, 11].

Recently, the use of steel as a material in the industrial world and machinery has developed rapidly. Steel in the market generally has limited mechanical performance. One example is SKD11 steel which only has a lardness of \$8-60 HV [13]. Though SKD11 steel is widely used as dies, forming, and cutting so it requires high hardness performance [13, 14].

The highest chemical content of SKD11 steel is carbon (C) [15]. The hardness of steel can also be increased by increasing the carbon content of the steel [16]. One of the ways to increase carbon content can be done by coating the steel with amorphous carbon [17]. The amorphous carbon layer is attractive to researchers because of its good mechanical properties such as low coefficient of friction, hardness and high durability [18]. The hardness performance of SKD11 steel can be improved by deposition of an amorphous carbon layer by plasma sputtering profess [19].

Previous research on deposition of carbon thin film on glass substrate using material target from battery carbon rods with plasma sputtering show that the carbon was successfully deposited onto glass substrate. It was proved by FTIR results, C-C and C=C was formed [1]. In the view of all these, argon plasma sputtering to deposition carbon thin film using material target from battery carbon rods may provide a new efficient approach to improve the mechanical properties of films. There is great scope to work on this topic further.

In the other studies, microstructural changes and hardness variations in SKD11 steel have been investigated during the processes of carbide dispersion (CD). However, the process of carbide dispersion carburizing requires high temperatures at 980 °C and the process takes a long time for 120 min. The process certainly requires a greater cost that plasma sputtering. Even though, plasma sputtering is more simple and cheaper than carburizing method to improve hardness performance of SKD11 steel. However, the investigation plasma sputtering process for hardening SKD11 steel was limited. On the other sides, SKD11 steel has limited hardness performance of 58-60 HV. Even though, the steel is commonly used for industrial purposes which require a high hardness performance. Therefore, 1 udies that are devoted to obtain the maximum average of hardness value of carbon thin films on SKD11 steel with optimization of argon gas power parameter on plasma sputtering.

### 2. Literature review and problem statement

Plasma is the fourth phase form of matter after solid, liquid, and gas [20]. Plasma is formed due to ionization. Plasma can be applied as a method for deposition of thin films [12]. One application of carbon deposition is carried out on steel. Synthesis of thin films has been carried out using plasma enhanced chemical vapor deposition, plate parallel hollow cathode plasma with radio frequency, and plasma sputtering.

Based on these 3 methods, plasma sputtering has several advantages compared to other methods such as high deposition rates, low substrate temperatures, and synthesis high quality of thin films [8, 11]. Plasma sputtering works by utilizing high energy of plasma species as bombers of target materials [21].

Steel that is often used for industry, generally has limited mechanical performance. Many of research are done to improve steel mechanical performance [19]. One of the examples is research of increasing the hardness value of AISI H13 steel. The results of research indicate that increasing the hardness value with the increasing carbon content of AISI H13 steel [22]. Besides AISI H13 steel, there is steel that often used in the industrial world, such as SKD11 steel [23]. SKD11 steel is often used for dies, forming, and cutting [15]. However, SKD11 steel still has weaknesses. SKD11 steel has low hardness, around 58–60 HV [13]. Based on these problems, research has to do to increase the flue of steel hardness. One of the ways is deposition carbon thin films on SKD11 steel with plasma sputtering.

Power is an important role in the process of plasma sputtering [19, 23]. The higher the power, the stronger the electric field that is formed, and the greater ion energy. If the energy of ion is greater than the binding energy of the target material's atoms, the atoms of the target material will be detached from the bonds of the atoms and move in all directions. The atom of the target material that comes out is called a sputtered atom [10]. Sputtered atom will be deposited on surface substrate and thin films structure that is formed will affect to the atoms of substrate [1].

A similar study about the effect of plasma sputtering RF power on diamond-like carbon thin films was previously had been carried out by Jongwannasiri et al. Based on the results of the study showed plasma treatment on DLC films surface influenced to thickness change, but not affect to structure of the films with various RF powers [11]. However, the limitation of this result didn't discuss about the effect of various plasma power on hardness of DLC films and only discuss the thickness of DLC films. Even though, Björling et al, found that the thicker deposited carbon thin film on substrate will have a high probability of carbon content [25]. In addition, Concepción et al, also found that the greater value of carbon content in carbon thin films, the greater value of hardness [16]. Therefore in this study, deposition carbon thin films with plasma sputtering for hardening SKD11 is done by using material target from battery carbon rods and determine effect power of plasma connected with hardness of carbon thin films on SKD11.

### 3. The aim and objectives of research

The aim of research 1 to investigate plasma sputtering process to increasing hardness of carbon thin films on SKD11 steel.

To achieve this aim, the following objectives are accomplished:

 to observe plasma power affected on hardness of carbon thin films on SKD11 steel.

### 4. Experimental method

### 4. 1. Sample preparation

Material target that used in this research was prepared by carbon rod from zinc-carbon ABC battery waste

(ABC Battery Industry, made in Indonesia). The carbon rod was cut into reach diameter 8 mm and length 55 mm. Then, the carbon rod was cleaned by ultrasonication with 40 kHz and 360 W in soap, solution for 1 minute. The cleaned carbon rod was dried in the oven at 300  $^{\circ}\mathrm{C}$  for 2 hours. The substrate used is SKD11 steel. Before plasma sputtering process, the substrate was cleaned by technical alcohol.

### 4. 2. Deposition thin film

Carbon films were deposited using plasma sputtering. Plasma is generated by low frequency generator (LFG) 40 KHz. The plasma system has diameter chamber of 250 mm. The carbon rod as material target was placed at the electrode. Carbon rods as a target material are placed on the electrodes. The distance between the target material and SKD11 steel is kept at 1.7 cm. The argon gas was introduced with flow rate of 20 mL/min into the chamber after vacuum process of 1.5 hours. The power used for generation varies 300 W, 340 W, 380 W, 420 W and 460 W. The deposition is done for 2 hours, keeping the temperature at 300 °C. The illustration scheme of the plasma sputtering system used in this research is shown in Fig. 1 and plasma sputtering process on vacuum chamber shown in Fig. 2.




Fig. 1. Scheme of the plasma sputtering system




Fig. 2. Plasma sputtering process on vacuum chamber

### 4. 3. Characterization

The heliness value of SKD11 steel that has been deposited with carbon thin films on SKD11 with power treatment was tested using micro hardness Vickers at three different test points shown as Fig. 3. The hardness value of SKD11 steel is obtained by taking the average hardness value from measurements at three test points that have been done pre-

1 busly. The content and morphology of the carbon rod and thin films carbon on SKD11 steel with plasma sputtering treatment on optimum power parameters of 340 W was measured using scanning electron microscope/energy dispersive using X-ray (SEM-EDX).




Fig. 3. Micro hardness vickers at three different test points on carbon thin films on SKD11 steel


### 5. Research results of hardness value of carbon thin films on SKD11 steel and SEM EDX

The hardness value of SKD11 steel that has been deposited with carbon film with power variations was tested with micro hardness Vickers to determine the effect of power on the plasma sputtering process on the hardness of SKD11 steel. The results of the SKD11 steel hardness test using micro hardness Vickers are shown in Table 1, Fig. 4.

### Table 1 The hardness value of carbon thin films on SKD 11 steel after power of plasma sputtering treatment based on the microhardness Vickers test

Test Point	Hardness Value (HV) Carbon thin films with Power							
	300 W	340 W	380 W	420 W	460 W			
1	253.1	328.3	279.8	265.3	248.8			
2	262.2	309.1	268.1	260.2	247.7			
3	262.8	312.7	283.2	271.5	256.4			
Average of hardness	259.3	316.7	277.0	265.7	251.0			

### Average of hardness value of SKD 11 steel after power of plasma sputtering treatment based on the microhardness vickers test



→ Average of hardness value

Linear (Average of hardness value)

Fig. 4. Graph of hardness value of SKD11 Steel with power treatment

SEM imaging of carbon rods and carbon thin film on SKD11 after plasma treatment with optimum power parameter of 340 W shown in Fig. 5, 6.

SEM observation was carried out on the outermost part of carbon rods from ABC battery waste shown as Fig. 5. The red line of Fig. 5 is an area that shows composition of battery carbon rods shown as Table 2. Based on SEM-EDX results shown as Table 2, atomic carbon level of carbon rods has  $81.94\,\%$ .




Fig. 5. SEM imaging of carbon rods outer layer from ABC battery waste

Table 2
Compositions of battery carbon rods based on SEM-EDX
results

Element	Atomic %
C	81.94
0	13.98
Al	0.98
Si	1.16
Cl	0.54
K	0.34
Ca	0.43
Fe	0.63




Fig. 6. SEM imaging of carbon thin film on SKD11 steel after plasma sputtering treatment with optimum power parameter of 340 W

Table 3 shown carbon purity level of thin film on SKD11 steel after plasma sputtering treatment with optimum parameter of  $340~\rm W.$ 

Table 3
Compositions of carbon thin film on SKD11 steel after
plasma sputtering treatment with optimum power parameter
of 340 W based on SEM-EDX results

Element	Atomic %
Cr	15,76
Mn	1,32
Fe	54.51
Ni	5.73
Si	0,90
0	8,32
С	13,36
V	0,11

### 6. Discussion of the research results of hardness value of carbon thin films on SKD11 steel and SEM EDX

It follows from Table 1 that the variation of power on plasma from 1300 to 340 Watt increases the average of hardness value of carbon thin films on SKD11 steel, from 259.3 HV increased to 316.7 HV. However, power variations from 380 W, 420 W and 460 W have decreased hardness at 380 W to 460 W, from 277 HV to 251 HV. The treatment of power on plasma sputtering with highest average hardness value is obtained at power of  $340\,\mathrm{W}$  with  $361.7\,\mathrm{HV}$ . Fig. 4 shows that downtrend on graph of relationship SKD11 steel with power treatment. Based on the graph shown as Fig. 4, the hardness value has a tendency to decrease when the power on plasma sputtering increases. This is because power is related to plasma energy. The greater the power causes the greater argon ion energy. It causes the transfer of energy from plasma to carbon atoms. As a consequence, carbon atoms have more energy when the power on plasma sputtering is greater. High-energy carbon atoms will tend to re-reflect or reflect rather than forming bonds or deposited on the surface. While at too low a power the carbon atom does not have enough energy to form carbon bonds on surface of SKD11 steel. At optimum power, the carbon atom is not too energetic but the energy it possesses is also not too small. As a result, the carbon bonds formed on the surface SKD11 steel are higher than the other power parameters. It can be seen in Fig. 7 which shows an illustration of the movement of carbon atoms from carbon rods on SKD11 steel substrates.

As follows from the Table 2 and Fig. 4, however, if this refers to previous research that solved the problem of successfully depositing carbon of carbon rod from waste of ABC battery which has 81.94% of atomic carbon on a glass substrate using plasma sputtering [1]. Based, on these results, the carl of carbon rods from ABC battery waste has potential to be used as a target material for deposition of carbon thin films on SKD11 steel substrate.

Based on surface morphology, the outer surface of the carbon rod has a rougher shape than the outer surface of carbon thin films on SKD11 (Fig. 5, 6.). Based on the previous reference, the atomic carbon of SKD11 steel without treatment is 1.5%. Table 3 shows that if the atomic carbon of thin film on SKD11 after plasma treatment with optimum power parameter of 340 W compared with the carbon con-

tent of SKD11 steel with 1 treatment based on reference. Atomic carbon content in thin films on SKD11 with power treatment (13.36%) is higher than atomic carbon content on SKD11 steels without treatment (1.5%). Carbon impurities in thin films affect the value of hardness. High carbon impurities indicate that concentrations of atoms that are not same type are high. The higher carbon impurities deposited on SKD11 steel, cause more smaller possibility bonding between carbon and carbon on SKD11 steel. This bond is covalent bonds which is a strong bond and requires high energy to break the bond. More covalent bonds cause increasing the hardness of carbon thin films on SKD11.




Fig. 7. Main signature: a- deposition of carbon atoms at low power; b- deposition of carbon atoms at optimum power; c- deposition of carbon atom at high power; e- carbon atom; e- direction of carbon atom; e- atom of SKD11 steel

The advantages of this research compared to the other similar research, studies that are more discuss the effect of LFG plasma sputtering power with hardness thue of SKD11 steel and obtain the maximum average of hardness value of carbon thin films on SKD11 steel with optimization of argon gas power thrameter on plasma sputtering. Previous research, about the effect of plasma sputtering RF power on diamond-like carbon thin films had been carried out. Towever, the limitation of this result didn't discuss about the effect of various plasma power on hardness of DLC films and only discuss the thickness of DLC films [25]. The other

studies also have been carried out by deposition of carbon thin film with LFG plasma sputtering power treatment of 220 W, 260 W, 320 W, and 340 W on glass using battery carbon rods as target. But, the result only discuss about FTIR results of carbon sputtering with various power [1].

The shortcomings and restrictions of the research, SKD11 without treatment are not tested by micro hardness Vickers to determine the hardness value. So that comparison of the hardness value of SKD11 steel without treatment is based on previous research as references and SEM-EDX is only tested on the most optimum power parameters of 340 W. Plasma sputtering system in this study still uses manual systems and there are no pressure gauge sensors of plasma sputtering system.

There are several things that can be developed in this research. Increased range of power variations  $(100-500\,\mathrm{W})$  and measure the hardness value for each power variations. Pressure gauge can be added to know the value of pressure in the chamber of plasma sputtering system.

### 7. Conclusion

Experiment study of deposition carbon thin film on SKD11 with power on plasma sputtering treatment had been investigated to dete 1 ine hardness performance. Based on micro hardness test, the optimum power treatment obtained at 340 Watt with the highest average hardness value is 316.7 HV. At optimum power, the carbon atom is not too 1 ergetic but the energy it possesses is also not too small. Based on SEM-EDX observation, it can be described that comparison of atomic carbon from carbon rods without treatment (1.5%) and carbon thin films on SKD11 with optimum power treatment (13.36%) show different value. Number of atomic carbon of thin films on SKD11 with power treatment is higher than atomic carbon of carbon rods without treatment.

### References

- Purkuncoro, A. E., Santjojo, D. J. D. H., Irawan, Y. S., Soenoko, R. (2019). Deposition of Carbon Thin Film by Means of a Low-Frequency Plasma Sputtering Using Battery Carbon Rods as a Target. IOP Conference Series: Materials Science and Engineering, 515, 012041. doi: https://doi.org/10.1088/1757-899x/515/1/012041
- Klotz, K., Weistenhöfer, W., Neff, F., Hartwig, A., van Thriel, C., Drexler, H. (2017). The Health Effects of Aluminum Exposure. Deutsches Aerzteblatt Online, 114 (39), 653–659. doi: https://doi.org/10.3238/arztebl.2017.0653
- Tanong, K., Blais, J.-F., Mercier, G. (2014). Metal Recycling Technologies for Battery Waste. Recent Patents on Engineering, 8 (1), 13–23. doi: https://doi.org/10.2174/1872212108666140204004041
- Nindhia, T. G. T., Surata, I. W., Atmika, I. K. A., Negara, D. N. K. P., Artana, I. P. G. (2015). Processing Carbon Rod from Waste of Zing-Carbon Battery for Biogas Desulfurizer. Journal of Clean Energy Technologies, 3 (2), 119–122. doi: https://doi.org/10.7763/jocet.2015.v3.179
- Nindhia, T. G. T., Surata, I. W., Atmika, I. K. A., Negara, D. N. K. P., Artana, I. P. G. (2015). Processing Carbon Rod from Waste of Zing-Carbon Battery for Biogas Desulfurizer. Journal of Clean Energy Technologies, 3 (2), 119–122. doi: https://doi.org/10.7763/jocet.2015.v3.179
- Erdemir, A., Donnet, C. (2006). Tribology of diamond-like carbon films: recent progress and future prospects. Journal of Physics D: Applied Physics, 39 (18), R311–R327. doi: https://doi.org/10.1088/0022-3727/39/18/r01
- Chu, P. K., Li, L. (2006). Characterization of amorphous and nanocrystalline carbon films. Materials Chemistry and Physics, 96 (2-3), 253–277. doi: https://doi.org/10.1016/j.matchemphys.2005.07.048
- Mori, T., Sakurai, T., Sato, T., Shirakura, A., Suzuki, T. (2016). Growth process of hydrogenated amorphous carbon films synthesized by atmospheric pressure plasma enhanced CVD using nitrogen and helium as a dilution gas. Japanese Journal of Applied Physics, 55 (4), 045503. doi: https://doi.org/10.7567/jjap.55.045503
- Wen, F., Liu, J., Xue, J. (2017). The Studies of Diamond-Like Carbon Films as Biomaterials: Review. Colloid and Surface Science, 2 (3), 81–95.

- Abdelrahman, M. M. (2015). Study of Plasma and Ion Beam Sputtering Processes. Journal of Physical Science and Application, 5 (2). doi: https://doi.org/10.17265/2159-5348/2015.02.007
- Plasma Technology (2007). Available at: https://pdf.directindustry.com/pdf/diener-electronic/plasma-technology-diener-electronic/ 50802-410101.html
- Hammadi, O. (2015). Fundamentals of Plasma Sputtering. Nanophotonics and Nanodevices Fabricated by Magnetron Sputtering Technique. doi: http://doi.org/10.13140/RG.2.1.3855.5605
- General Catalog of YSS Tool Steels (2015). Available at: https://www.hitachi-metals.co.jp/e/products/auto/ml/pdf/yss\_tool\_steels\_d.pdf
- Yu, Z., Wang, Z. G., Yamazaki, K., Sano, S. (2006). Surface finishing of die and tool steels via plasma-based electron beam irradiation. Journal of Materials Processing Technology, 180 (1-3), 246–252. doi: https://doi.org/10.1016/j.jmatprotec.2006.06.014
- Kong, J. H., Sung, J. H., Kim, S. G., Kim, S. W. (2006). Microstructural Changes of SKD11 Steel during Carbide Dispersion Carburizing and Subzero Treatment. Solid State Phenomena, 118, 115–120. doi: https://doi.org/10.4028/www.scientific.net/ssp.118.115
- De la Concepción, V. L., Lorusso, H. N., Svoboda, H. G. (2015). Effect of Carbon Content on Microstructure and Mechanical Properties of Dual Phase Steels. Procedia Materials Science, 8, 1047–1056. doi: https://doi.org/10.1016/j.mspro.2015.04.167
- Calik, A., Duzgun, A., Sahin, O., Ucar, N. (2010). Effect of Carbon Content on the Mechanical Properties of Medium Carbon Steels. Zeitschrift Für Naturforschung A, 65 (5), 468–472. doi: https://doi.org/10.1515/zna-2010-0512
- Jones, B. J., Anguilano, L., Ojeda, J. J. (2011). Argon plasma treatment techniques on steel and effects on diamond-like carbon structure and delamination. Diamond and Related Materials, 20 (7), 1030–1035. doi: https://doi.org/10.1016/j.diamond.2011.06.004
- Mróz, W., Burdyńska, S., Prokopiuk, A., Jedyński, M., Budner, B., Korwin-Pawlowski, M. L. (2009). Characteristics of Carbon Films Deposited by Magnetron Sputtering. Acta Physica Polonica A, 116, S-120–S-122. doi: https://doi.org/10.12693/aphyspola.116.s-120
- Miyamoto, K. (2000). Fundamentals of Plasma Physics and Controlled Fusion. Available at: http://people.physics.anu.edu.au/ -jnh112/AIIM/c17/Miyamoto.pdf
- González, J. M., Bertran, E. (2015). Mechanical and Surface Characterization of Diamond-Like Carbon Coatings onto Polymeric Substrate. Available at: https://arxiv.org/ftp/arxiv/papers/1509/1509.08512.pdf
- Telasang, G., Dutta Majumdar, J., Wasekar, N., Padmanabham, G., Manna, I. (2015). Microstructure and Mechanical Properties
  of Laser Clad and Post-cladding Tempered AISI H13 Tool Steel. Metallurgical and Materials Transactions A, 46 (5), 2309–2321.
  doi: https://doi.org/10.1007/s11661-015-2757-z
- Aizawa, T., Fukuda, T. (2013). Oxygen plasma etching of diamond-like carbon coated mold-die for micro-texturing. Surface and Coatings Technology, 215, 364–368. doi: https://doi.org/10.1016/j.surfcoat.2012.07.095
- Jongwannasiri, C., Watanabe, S. (2014). Effects of RF Power and Treatment Time on Wettability of Oxygen Plasma-Treated Diamond-like Carbon Thin Films. International Journal of Chemical Engineering and Applications, 5 (1), 13–16. doi: https://doi.org/10.7763/jicea.2014.v5.342
- Björling, M., Larsson, R., Marklund, P. (2014). The Effect of DLC Coating Thickness on Elstohydrodynamic Friction. Tribology Letters, 55 (2), 353–362. doi: https://doi.org/10.1007/s11249-014-0364-6

### THE EFFECT OF LFG PLASMA SPUTTERING POWER ON HARDNESS OF CARBON THIN FILMS ON SKD11 STEEL USING TARGET MATERIAL FROM BATTERY CARBON RODS

**ORIGINALITY REPORT** 

8%

10%

0%

2%

SIMILARITY INDEX

INTERNET SOURCES

**PUBLICATIONS** 

STUDENT PAPERS

**PRIMARY SOURCES** 



journals.uran.ua

Internet Source

8%

Exclude quotes

On

Exclude matches

< 2%

Exclude bibliography

On